# Anaconda Sealtite® FG-Clean

use in food- and beverage industry





## **FG-Clean**, white

Highest requirements to cleanliness and cleaning.

Protection tubes from reinforced galvanised steel band with spiral wound, latched (from 1 1/2" doubkle folded profile -Agraff) and a thick smooth thermoplastic PVC jacket.

# Application

- Food industry milk- and meat products
- Packaging of food machines
- Beverage industry
- Pharmaceutical industry
- Biotechnology
- Chemical industry

#### Material

galvanised steel Outer sheat material: Special-PVC according to FDA CFR 21 and NSF 51 (USA-Norm)

# **Properties**

- liquid tight
- the smooth surface prevents to adhere harmful micro organisms
- easy and fast cleaning because of the smooth surface
- suitable for high pressure steam cleaning
- resistant against chemical cleaning supplies
- high flexible
- · high tensile and pressure proof

# **Technical data**

Protection class: IP 67 - in conjunction with the suitable tube connectors

Temperature range: -20°C up to +60°C Temperature range temporary uo to +80°C

#### Note

Suitable connection glands: LT-FG-Clean (up to M50), also possible LT-straight, LT-45°, LT-90°, LT-E-UI-straight, LT-E-UI-90°

Part-no. white	trade size inch	Inner-Ø mm	Outer-Ø mm	Bending radius static	Bending radius dynamic	unit m
906883	3/8″	12,6	17,8	60	85	30
906425	1/2″	16,0	21,1	75	110	30
906855	3/4"	21,0	26,4	90	140	30
906856	1"	26,5	33,1	120	170	30
906857	1 1/4″	35,1	41,8	135	215	15
906858	1 1/2″	40,3	47,8	165	250	15
906927	2″	51,6	59,9	210	300	15

Dimensions and specifications may be changed without prior notice.

